


Anziehvorschrift für Zylinderkopf	073.942	 Das Original
Tightening Instructions for Cylinder Head		
Instructions de serrage pour culasse		
Prescripciones de apriete para culatas		
passend für / suitable for adaptable à / adaptable a		Renault, Nissan, Opel

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



258.180
M 12x1,5x117,5



Anziehen/ * 30 Nm
Tightening/ 30 Nm
Serrage/ ► 180 ° +/-25°
Apriete

Zeichenerklärung / Explanations / Explication / Explicacion

*	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
►	Drehwinkel	torque angle	angle de serrage	ángulo de giro

Motortyp / Engine type / Type de moteur / Tipo de motor

Ø 83,8 mm; \pm : 0,7 mm

Mot: F4P 720, 722, 760, 770, 771, 773-775
F4R 700, 701, 712-715, 720, 722, 730, 738,
740, 741, 744, 770, 771, 780, 790, 791, 820
1,8 16 V / 2,0 16 V

Espace, Scenic, Laguna, Megane, Trafic, Vivaro

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

073.942